

This technical drawing shows a cross-section of a retaining wall. The wall has a total height of 5.000 units. It features a concrete deck (Betondecke) at the top, which is 0.815 units wide. A railing (Geländer) is positioned on top of the deck. The wall's base is 0.856 units wide. The wall face is labeled "Spundwand, Einbindung nach statischer Erfordernis". The ground behind the wall is filled with gravel (Gefälleaufüllung). The ground surface is shown as a dashed red line with a slope of approximately 1:10. The original ground level is indicated by a solid black line. A road (Weg) is located to the right of the wall. Other dimensions include 0.500 units for the width of the concrete deck above the railing, 0.930 units for the width of the gravel fill area, and 0.815 units for the width of the concrete deck below the railing.

Draufsicht
M 1:100

befahrbare Berme

4.500

5.100

5.000

7.000

45°

Wasserbausteine zur Böschungssicherung

Stauhaltungsdamm

0.600

A

Plangrundlage:					
D					
C					
B					
A					
Anl.	Schlusss	Nutzen			
Projekt				Planart:	Gemeinungsplanung

Zauner GmbH
Technisches Büro Zauner GmbH
Marktstraße 35, A-4090 Engelhartzell
ezell@zb-fluss.at

Landschaft + Plan Passau
Passauer Straße 21, 94127 Neuburg a. Inn
info@landschaftunplan-passau.de

2.8	Innkraftwerk Ering-Frauenstein Durchgängigkeit und Lebensraum Umgebungsgewässer
Maßstab: 1:100	

Datum		Name	
Gedr:	25.02.2016	Haller	
Gedr:	25.02.2016	Ringler	
Gedr:			
KKS-gedr:			
KKS-gedr:			
Wegkreuzung Draufsicht, Schritte			
Plangröße: A2	Maßstab:	CAD-Anwendung:	GSD:
		GSD-Info:	

[illegible]